

### Product type designation

### PC adapter USB A2

PC ADAPTER USB A2 USB-ADAPTER (USB V2.0) FOR CONNECTING A PG/PC OR NOTEBOOK TO SIMATIC S7 VIA PROFIBUS OR MPI USB CABLE 5M INCLUDED MPI-KABEL 0,3M CAN BE USED UNDER WINXP/VISTA/ WINDOWS 7 32/64BIT



### Transmission rate

#### Transfer rate

- at the 1st interface / acc. to PROFIBUS

9.6 kbit/s ... 12 Mbit/s

### Interfaces

#### Number of electrical connections

- at the 1st interface / acc. to PROFIBUS

1

#### Number of interfaces / acc. to USB

1

#### Type of electrical connection

- at the 1st interface / acc. to PROFIBUS
- of the USB interface

9-pin Sub-D socket (RS 485)

Standard-B socket

#### Standard for interfaces / USB 2.0

Yes

### Supply voltage, current consumption, power loss

#### Type of voltage / of the supply voltage

DC

#### Type of voltage supply / optional external supply

No

#### Supply voltage

- from USB
- Note

5 V

Supply direct from USB

Relative symmetrical tolerance / at DC	
<ul style="list-style-type: none"> <li>• at 5 V</li> </ul>	5 %
Consumed current	
<ul style="list-style-type: none"> <li>• from USB</li> </ul>	0.2 A
Power loss [W]	1 W

### Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> <li>• during storage</li> <li>• during transport</li> </ul>	0 ... 60 °C -40 ... +70 °C -40 ... +70 °C
Relative humidity / at 30 °C / during operation / maximum	95 %
Protection class IP	IP20

### Design, dimensions and weight

Module format	USB V2.0 adapter
Width	58 mm
Height	26 mm
Depth	105 mm
Net weight	0.365 kg
Mounting type / 35 mm DIN rail mounting	No
Number of plug-in cards of same design / plug-in / per PC station	1
Number of units / Note	-

### Performance data

### Product functions / Diagnosis

Product function	
<ul style="list-style-type: none"> <li>• Port diagnostics</li> </ul>	Yes

### Standards, specifications, approvals

Standard	
<ul style="list-style-type: none"> <li>• for EMC</li> <li>• for safety / from CSA and UL</li> <li>• for emitted interference</li> <li>• for interference immunity</li> </ul>	2004/108/EC cULus, UL 60950-1, CSA22.2 EN 61000-6-3, EN 61000-6-4 EN 61000-6-1, EN 61000-6-2
Certificate of suitability	
<ul style="list-style-type: none"> <li>• CE marking</li> <li>• C-Tick</li> </ul>	Yes Yes

### Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> <li>• to website: Selector SIMATIC NET SELECTION TOOL</li> </ul>	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>

- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/simatic-net>  
<http://www.siemens.com/industrial-controls/mall>  
<http://www.siemens.com/industry/infocenter>  
<http://automation.siemens.com/bilddb>  
<http://www.siemens.com/cax>  
<https://support.industry.siemens.com>

## Security information

### Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

**last modified:**

08/11/2016